

**CRYSTAL OSCILLATOR (SPXO)**  
**OUTPUT : CMOS**

**SG-210S\*B**

- Frequency range : 2 MHz to 60 MHz
- Supply voltage : 1.5 V Typ. / 1.8 V Typ. / 2.5 V Typ. / 3.3 V Typ.
- Current consumption : 0.9 mA Typ.  
(SEB: 1.8 V No load condition 48 MHz)
- Function : Standby( $\overline{ST}$ )
- External dimensions : 2.5 × 2.0 × 0.8 mm
- Operation temperature : +105 °C / +125 °C



Product Number (please contact us)  
Q33210Bx0xxxx00



Actual size

**Specifications (characteristics)**

Item	Symbol	SG-210SGB	SG-210SEB	SG-210SDB	SG-210SCB	Conditions / Remarks
Output frequency range	f <sub>0</sub>	2 MHz to 32 MHz	2 MHz to 60 MHz			
Supply voltage	V <sub>CC</sub>	1.5 V Typ. 1.3 V to 1.7 V	1.8 V Typ. 1.6 V to 2.2 V	2.5 V Typ. 2.2 V to 3.0 V	3.3 V Typ. 2.7 V to 3.6 V	
Storage temperature	T <sub>stg</sub>	-40 °C to +125 °C				Storage as single product.
Operating temperature	T <sub>use</sub>	-40 °C to +85 °C / -40 °C to +105 °C / -40 °C to +125 °C				
Frequency tolerance	f <sub>tol</sub>	F: ±20 × 10 <sup>-6</sup>				-10 °C to +60 °C, f <sub>0</sub> ≤ 32 MHz, V <sub>CC</sub> ±10%, except reflow drift.
		B: ±50 × 10 <sup>-6</sup> , C: ±100 × 10 <sup>-6</sup>				-20 °C to +70 °C
		L: ±50 × 10 <sup>-6</sup> , M: ±100 × 10 <sup>-6</sup>				-40 °C to +85 °C
		Y: ±50 × 10 <sup>-6</sup> , W: ±100 × 10 <sup>-6</sup>				-40 °C to +105 °C
		Z: ±100 × 10 <sup>-6</sup> , X: ±150 × 10 <sup>-6</sup>				-40 °C to +125 °C
Current consumption	I <sub>CC</sub>	1.0 mA Max.	1.6 mA Max.	2.4 mA Max.	3.0 mA Max.	No load condition
		–	2.0 mA Max.	3.0 mA Max.	4.0 mA Max.	No load condition +105 °C, +125 °C
Stand-by current	I <sub>std</sub>	0.3 µA Max.	0.5 µA Max.	1.0 µA Max.	1.0 µA Max.	$\overline{ST}$ = GND
		–	1.6 µA Max.	2.4 µA Max.	3.0 µA Max.	$\overline{ST}$ = GND +105 °C, +125 °C
Symmetry	SYM	45 % to 55 %	45 % to 55 %	45 % to 55 %	45 % to 55 %	2 MHz ≤ f <sub>0</sub> ≤ 16 MHz
		40 % to 60 %	–	–	–	16 MHz < f <sub>0</sub> ≤ 32 MHz
		–	40 % to 60 %	40 % to 60 %	–	32 MHz < f <sub>0</sub> ≤ 60 MHz
		–	–	40 % to 60 %	–	+105 °C, +125 °C
Output voltage	V <sub>OH</sub>	90 % V <sub>CC</sub> Min.				I <sub>OH</sub> = -1 mA
	V <sub>OL</sub>	10 % V <sub>CC</sub> Max.				I <sub>OL</sub> = 1 mA
Output load condition(CMOS)	L <sub>CMOS</sub>	15 pF Max.				
Input voltage	V <sub>IH</sub>	80 % V <sub>CC</sub> Min.				$\overline{ST}$ terminal
	V <sub>IL</sub>	20 % V <sub>CC</sub> Max.				
Rise time and Fall time	tr/ tf	5 ns Max.	4 ns Max.	3 ns Max.		+85 °C
		–	–	7 ns Max.		+105 °C, +125 °C
Start-up time	t <sub>str</sub>	3 ms Max.				t=0 at 90 % V <sub>CC</sub> (+105 °C, +125 °C : 5 ms Max.)
Frequency aging	f <sub>aging</sub>	±3 × 10 <sup>-6</sup> / year Max.				+25 °C, First year, V <sub>CC</sub> =1.5 V, 1.8 V, 2.5 V, 3.3 V


Product Name (Standard form) **SG-210 S G B 27.000000MHz L**  
 ① Model    ② Function (S: Standby)  
 ③ Supply voltage    ④ Frequency  
 ⑤ Frequency tolerance

③ Supply voltage	
G	1.5 V Typ.
E	1.8 V Typ.
D	2.5 V Typ.
C	3.3 V Typ.

⑤ Frequency tolerance		*Except for SGB
F	±20 × 10 <sup>-6</sup>	-10 to +60 °C (f <sub>0</sub> ≤ 32 MHz)
B	±50 × 10 <sup>-6</sup>	-20 to +70 °C
C	±100 × 10 <sup>-6</sup>	-20 to +70 °C
L	±50 × 10 <sup>-6</sup>	-40 to +85 °C
M	±100 × 10 <sup>-6</sup>	-40 to +85 °C
Y*	±50 × 10 <sup>-6</sup>	-40 to +105 °C
W*	±100 × 10 <sup>-6</sup>	-40 to +105 °C
Z*	±100 × 10 <sup>-6</sup>	-40 to +125 °C
X*	±150 × 10 <sup>-6</sup>	-40 to +125 °C

**External dimensions**

(Unit:mm)



**Footprint (Recommended)**

(Unit:mm)

